

# Inverter INVW400

- case for wall mounting
- small and strong
- without 50 Hz transformer
- potential free
- sinewave
- short-circuit protected
- overload protected

Picture may differ from actual device



## Specifications

### General

Electrical safety	EN 60950, VDE 0805 overload and short-circuit protected
Efficiency	about 85%, nominal load
Galvanic isolation	3.75 kV <sub>DC</sub>
EMC (emission)	EN 50081-1 Curve EN 55022B
EMC (immunity)	EN 50082-2
Operating temperature	-25 to +45°C non condensing

### Input

INVW400-24	24 (19 - 31) V <sub>DC</sub>
------------	------------------------------

### Output

Voltage	230 V <sub>AC</sub> (115V <sub>AC</sub> upon request)
Frequency	50 Hz, sinewave processor controlled (60Hz upon request)
Power	400 VA, 320W
Power factor	0.8
Load range	0 - 100%
Crestfactor	>2.5
Harmonic distortion	<3%

### Signals/Operation

Optical signals	Power/PG, Overload/OVL
Signal output	voltage free alarm contact
Operation	switch

### Optional:

Control input	optocoupler input for remote operation
---------------	---

### Warranty

24 months

### Housing

Size	wall mounting case
(W x D x H)	270 x 115 x 255 (mm)
Weight	app. 5kg
Classification	IP 54
Ventilation	convection via heatsink on wall side

### Electrical connections

Connectors	bottom connectors
DC-Input	Harting connector HAN Q5, 3-pole
AC-Output	Harting connector HAN Q5, 3-pole
Signals	Binder round connector DIN 45322 (Harting HAN 80 5-pole opt.)
Earthing	via Harting HAN Q5 (DC-IN), earthing screw on the case

### Order Code

e.g. INVW400-24 - 230 - 1

Type	P / VA	U <sub>IN</sub> / VDC	U <sub>OUT</sub> / VAC	Options
INV	400	24	230	1, 5
			115	

Separate values by hyphen (-), append options where applicable

Options:

1: 60Hz f<sub>OUT</sub>

5: HAN 80 input for remote operation